

Chapter 13 - 2011

TOWN OF RIVERVIEW  
OCONTO COUNTY  
Ordinance #30 for  
Minimum Highway/Roadway Design Standards

Whereas, it is in the public interest for the Town of Riverview, Oconto County to establish minimum highway/roadway design standards for highways/roadways being constructed in the town to accommodate anticipated traffic and afford satisfactory access to police, firefighting, snow removal, sanitation, and road maintenance equipment;

NOW THEREFORE IT IS HEREBY ORDAINED BY THE TOWN BOARD OF SUPERVISORS OF THE TOWN OF RIVERVIEW, OCONTO COUNTY as follows:

**SECTION 1. Definitions.**

In order to clarify this ordinance the following definitions are applicable.

- A. Approach--that portion of road extending 100 feet on each side of a culvert or bridge.
- B. Base Course--the supporting base material of the highway/roadway, including shoulder.
- C. Drainage--the gradual drying of highway/roadway by system of ditches, trenches, channels, etc.
- D. Grade--the rate of ascent or descent of highway/roadway.
- E. Highway--the road or way over which the public generally has a right to pass, to include the complete right-of-way.
- F. Road Bed--the whole material laid in place and ready for travel.
- G. Roadway--the traveled portion of the highway.
- H. Surface 1/2--the top of the highway/roadway, or traveled surface.

**SECTION 2. Applicability.**

This ordinance shall be applicable to all highways/roadways laid out by the Town Board after adoption of this ordinance, including any highways/roadways dedicated in plats for proposed subdivisions submitted for review pursuant to Chapter 236 of the Wisconsin Statutes, (PLATTING LANDS AND RECORDING AND VACATING PLATS) any private highways/roadways being donated to the town, and any other highways/roadways being accepted by the town as public highways/roadways in the town.

**SECTION 3. Minimum Design Standards.**

The following minimum design standards shall apply under this ordinance:  
All town highways/roadways shall be classified as local roads unless designated by the town board as collector or arterial. The classification of all highways/roadways under this ordinance shall be within the complete discretion of the town board considering such factors as traffic count, character of anticipated traffic, and relation of highway/roadway to traffic patterns within the town and other highway/roadway systems. It is intended that local be the lowest traffic count, with access to private property as principal function.

Collector highways/roadways are intended to be developed areas. Arterials are intended to serve as corridors through the town serving intra-regional traffic movement.

	Residential With C/G*	Residential Without C/G*	Commercial/Industrial With C/G*	Commercial/Industrial Without C/G*
<u>Minimum R.O.W.***</u>	66'	66'	66'	66'

Minimum width of Base Course (including curb, gutter or shoulders)

Local	30'	28'	32'	32'
Collector	32'	32'	40'	50'
Arterial	40'	34'	40'	50'

<u>Improvement</u>	Residential With C/G*	Residential Without C/G*	Commercial/Industrial With C/G*	Commercial/Industrial Without C/G*
--------------------	--------------------------	-----------------------------	------------------------------------	---------------------------------------

Minimum Width of Surfacing

Local	30'	20'	32'	24'
Collector	32'	22'	40'	30'
Arterial	40'	24'	48'	48'

Maximum grade (percent)

Local**	10	10	8	8
Collector**	8	8	6	6
Arterial**	6	6	6	6

\*\*Minimum grade .5

Minimum Radius of Horizontal Curve (in feet)

Local	100	100	200	200
Collector	100	100	200	200
Arterial	300	300	400	400

Corner Radius at Intersections

15                    30                    15                    30

Maximum length of Vertical Curve

Local --100', but not less than 20' for each algebraic difference in grade

Collector-- 200', but not less than 50' for each one percent

Arterial -- 300', but not less than 50' for each algebraic difference in grade.

	Residential With C/G* Without C/G*		Commercial/Industrial With C/G* Without C/G*
--	---------------------------------------	--	---

Minimum Length of Tangents Between Reverse Curves

Local	100'	100'	200'	200'
Collector	100'	100'	200'	200'
Arterial	200'	200'	300'	300'

Minimum Sight Distance

Local	200'	200'	200'	200'
Collector	250'	250'	250'	250'
Arterial	300'	300'	300'	300'

Design Speed (miles per hour)

Local	30	30	30	30
Collector	35	35	35	35
Arterial	40	40	40	40

CUL-DE-SACS (permanent)

Maximum Length

Maximum desirable length of roads with cul-de-sacs is 1,000 feet. Through roads are most desirable.

Minimum R.O.W. Radius at Cul-De-Sacs

Local	60'	60'	60'	60'
-------	-----	-----	-----	-----

Minimum Base Course Radius

Local	40'	42'	40'	42'
-------	-----	-----	-----	-----

Minimum Pavement Radius

Local	40'	40'	40'	40'
-------	-----	-----	-----	-----

Base course must be of a quality, thickness, and composition suitable for the location, minimum 6" to 8" pit run material, topped with crushed aggregate at least 600 yards per mile.

### Surface Course

Surface course must consist of bituminous concrete composition suitable for anticipated traffic loads. The minimum amount of pavement necessary for acceptance must be at least 2 1/2" in thickness. (NOTE: These minimums may be reviewed and adjusted by the Town Board of Riverview, depending on local conditions).

### Ditching and Culverts.

The ditching of the roadway must be complete and have proper elevation to provide for adequate drainage. Any culverts necessary for proper drainage shall be installed after elevation and location is obtained from the Town Board. The minimum length of any culvert installed in a road bed shall be at least two feet greater than the base course width. Apron end walls shall be used. The diameter and length will be subject to the approval of the Town Board, after the amount of the flowage is determined. In no case shall the culvert be less than 18" in diameter.

### Bridges.

All bridges shall meet the minimum requirements of state and federal law. In the event it is decided by the Town Board, that the construction of a bridge would be of a size and cost; that it would create a hardship to the owner of land required to build said bridge, then the Town Board may proceed to accept the road, complete as required above, except that part extending 100 feet on each side of said bridge. This portion of the road shall be known as the approach. The approach will be accepted incomplete, with the reversion that the town will bill back to the owner a portion of the cost of construction of such bridge. The Town will proceed to build said bridge and approach with the help of bridge aid if available, and billing the balance not covered by the aid or portion to be billed back to the owner.

### Section 4. Authority for Higher Standards.

The road design standards in Section 3 as stated above are intended to be minimum design standards. The Town Board shall have the discretion to impose higher design standards where in the opinion of the Town Board local conditions require higher standards or anticipated traffic in quantity or quality will require higher standards.

### Section 5. Application for Determination of Applicable Standards

Any person may apply to the Town Board to determine what design standards should apply in a particular location, dividing the description of the proposed highway/roadway and proposed design standards being requested to be approved for any proposed highway/roadway being proposed to be built. no person shall commence construction of any highway/roadway anticipated to be turned over to the town without having written approval of the proposed highway/roadway design signed by the Town Board.

Section 6. Final Inspection and Acceptance by the Town Board.

Upon completion of the proposed highway/roadway, the Town Board will proceed to make final inspection, accepting or rejecting the highway/roadway as the case may be in the discretion of the Town Board. If the highway/roadway is rejected, then corrections must be made as stated by the Town Board before final inspection will be made again. If final acceptance is made by the Town Board, the owner or owners will turn over to the Town, a warranty deed free and clear of any liens necessary to convey free and clear title to the town for the highway/roadway.

\*With C/G means with curb/gutter; Without C/G means without curb / gutter.

\*\*\*R.O.W. means Right-of-Way.

Adopted by the Town Board this 16 <sup>th</sup> day of February, 19 99

Vernon Shaefer  
Town Chairperson

Barbara Trosch  
Town Supervisor

Edna Hoga  
Town Supervisor

Jeanie A. Whalen  
Town Clerk

Filed in the Office of the Town Clerk  
this 23rd day of February, 19 99